

IPSLPOE5M

Camera, IP, H.265, 5MP, POE, ColorVu, Bullet



Features:

1/2.8" Sony IMX335 CMOS sensor

5MP, Full HD resolution 2592 x 1944P

Ultra low illumination 0.001Lux

Day/Night (ICR), AWB, AGC, BLC, 2D/3D-DNR, IR-CUT

D-WDR, Motion Detection, Privacy Mask, Mirror

RTSP and Onvif 11.07 compatible

H.265/H.264 dual-stream media server

Easy-to-use P2P Cloud service

Multi web browser, PC Client, mobile APP remote access

Lightning protection 4000V

Strong water-proof housing, IP66

2PCS Soft & Warm Supplemental Light, Light distance: 25-30M

HD 2.8mm F1.0 true starlight lens

Technical Specifications:

Model	IPSLPOE5M
Image Sensor	1/2.8" SONY IMX335 CMOS
Effective Pixels	2592 (H) × 1944 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.001Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Indoor/Outdoor
BLC	Support
DNR	2D/3DDNR
Other	Motion Detection, Privacy Mask, Mirror, flip
Embedded Solution	Mstar 316DM
Video Standard	H.264/H.265
Video Resolution	Main Stream:15fps@ 5MP(2592*1944) ,25fps@ 4MP(2592*1520)
Sub Stream	VGA(640x480)/360P@25fps, etc.
Video Bitrates	32Kbps - 6Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a
OSD Overlay	Title and Time overlay
Leds	2PCS Soft & Warm Supplemental Light
Light Distance	25-30 M
Focal length	HD 2.8mm F1.0 true starlight lens
Protocol	HTTP/RTSP/FTP/NFS/SMTP/DHCP/NTP, etc.
P2P	Yes
Web	IE , Firefox, etc.
Media	CMS, Android, IOS
ONVIF	2.6compatible
Network Port	1-RJ45, 100Mbps,
Power Supply	POE ,12 VDC ± 10%
Power Consumption	<8W