

IPVFPOE5M

Camera, IP, H.265, 5MP, POE, Vary Focal, Bullet



Features:

1/2.8" Sony IMX335 CMOS sensor

5MP realtime resolution 2560x1944P

Low illumination 0.01Lux

Day/Night, AWB/MWB,BLC, HLC, 2D/3D-DNR,Shutter, IR-CUT

D-WDR,Mirror, rotate, Defogging

Multiply Style OSD Overlay,Motion Detection, Privacy Mask

RTSP and Onvif 17.06 compatible with many third-party NVR

H.264/H.265 dual-stream media server

Easy-to-use P2P Cloud service

Support user authentication, video data encryption

Support Alarm Snapshot to Email and FTP

Multiply WEB browser IE,Firefox 32bit ESR, PC Client, Mobile APP remote access

RJ45 100mbps network port, IEEE802.3af PoE

Lightning protection 4000V

Strong water-proofhousing, IP66

4 pcsIR Leds, IR distance 70-80meters

HD2.8-12MM Varifocal lens

Technical Specifications:

Model	IPVFPOE5M
Image Sensor	1/2.8" Sony IMX335 CMOS
Effective Pixels	5 megapixels
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual
BLC /HLC	Support
DNR	2D/3D DNR
Other	AGC,Motion Detection,OSD overlay
Video Standard	H.264/H.265
Main Stream Video Resolution	25fps@5MP(2592x1944)/4MP(2592x1520)/3MP, 30fps@1080P/720P
Sub stream:	25fps@D1/VGA/360P/CIF, etc.
Video Bitrates	512Kbps - 12Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a
Built-in Mic	Optional
OSD Overlay	Title and Time overlay
IR Led	4pcs IR Array
IR Distance	70-80M
Focal length	2.8-12mm Varifocal lens
PoE	Yes
Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.
P2P	Yes
Web	IE , Firefox (32bit esr), etc.
Media	CMS, Android, IOS
ONVIF	17.06 compatible
Network Port	1-RJ45, 100Mbps,POE optional
Power Supply	12 VDC \pm 10%
Power Consumption	< 8 W