

Omega bracket intermediate - HDG

The Omega intermediate bracket is used to secure the fencing wires onto the Omega insulators. The intermediate brackets are only used in straight wire runs. The Omega system utilises the mechanical strength of an existing fence to reduce the cost of constructing a complete new system.



Features:

- Robust design for intermediates posts
- Easy to transport reducing handling time and transport costs
- Holes every 100mm to accommodate the Omega insulators (Also available in 91mm Hot dip galvanised)
- Easy to transport reducing handling time and transport costs

Specifications:

Finish: Hot dip galvanised

Steel thickness: 1 mm

Lengths (100mm spacing): 0.9m, 1.2m, 1.5m, 1.8m, 2.1m, 2.4m, 3m

Hole spacing: 100 mm and 91 mm

Lengths (91mm spacing): 2.4m, 3m

<https://www.nemtek.co.za/CommercialSecurity/Fencing-Brackets-Omega/omega-bracket.aspx>

Stock Code	Name	Description
EY-PRHDIP0900/1	Omega bracket intermediate - HDG	Free Standing - Omega - 0.9m-Hot Dip
EY-PRHDIP1200/1	Omega bracket intermediate - HDG	Free Standing - Omega - 1.2m-Hot Dip
EY-PRHDIP1500/1	Omega bracket intermediate - HDG	Free Standing - Omega - 1.5m-Hot Dip
EY-PRHDIP1800/1	Omega bracket intermediate - HDG	Free Standing - Omega - 1.8m-Hot Dip
EY-PRHDIP2100/1	Omega bracket intermediate - HDG	Free Standing - Omega - 2.1m-Hot Dip
EY-PRHDIP2400/1	Omega bracket intermediate - HDG	Free Standing - Omega - 2.4m-Hot Dip
EY-PRHDIP3000/1	Omega bracket intermediate - HDG	Free Standing - Omega - 3.0m-Hot Dip

SP-PRHD/24/91/1	Omega bracket intermediate - HDG	Free Standing-AU Omega-2.4m-HDG-91mm*1mm
SP-PRHD/30/91/1	Omega bracket intermediate - HDG	Free Standing-AU Omega-3.0m-HDG-91mm*1mm